

Power Cleaning Solutions

Formulated for use with POWERBOSS equipment and beyond.

TIRE MARK REMOVER

Heavy Duty Citrus Solvent Degreaser

- Contains 70% Citrus Solvents
- Removes Tire Marks on Concrete Floors
- Water Rinsable
- Also effective for removing Asphalt, Tar, Adhesives, Gums and Curing Membranes from a Variety of Surfaces.

DIRECTIONS FOR REMOVING TIRE MARKS:

- Use Straight, do not dilute.
- Apply Tire Mark Remover directly to tire marks with a low pressure pump-up sprayer or similar equipment.
- Apply enough to thoroughly wet the tire marks. Allow to dwell on tire marks for 5-10 minutes.
- Double scrub floor with PowerBoss Heavy Duty Degreaser or Powerboss Citrus Degreaser diluted 6-10 oz/gal.
- First pass, apply solution and scrub with squeegee up and vacuum off. On second pass, apply more cleaning solution with scrubber on and pick up spent solution with squeegee and vacuum.

Do not put Tire Mark Remover directly into Scrubber solution tank.

NOTE: Tire Mark Remover is a strong solvent and will attack many plastics. Test before use. It should not be used in the solution tank of automatic scrubbers or carpet extractors. As with other solvent cleaners, rubber gloves should be worn when working by hand and breathing spray mist should be avoided.

PowerBoss®

The Power of Clean

PowerBoss Tire Mark Remover is a heavy-duty solvent cleaner formulated with 70% natural d-Limonene (citrus solvent). Use to remove rubber tire marks from concrete floors. It can also be used to remove tar, asphalt, grease, oily soils, cut-back adhesive, gum, etc. from a variety of surfaces.



Specifications

Appearance: Amber liquid, citrus odor

pH: 10.2 ± .2

Specific Gravity: 0.89

Flashpoint: 120°F

Viscosity: Low

Dilution: Tire Marks: Use straight (Do not dilute)

Solvency: Excellent

Rinseability: Very good

Phosphate Builders: None

Chlorinated Solvents: None

Petroleum Distillates: None

Storage Stability: Store between 45° and 100°F.

Freeze/Thaw Stability: Freezes below 20°F. If chilled or frozen, thaw & stir well. Inspect for damage.

Shipping Classification: Flammable liquid, N.O.S. (Containing Terpene), class 3. UN 1993 Packaging Group: III

HMIS Hazard Rating for Concentrate

Health	1	0-Least
Flammability	0	1-Slight
Reactivity	0	2-Moderate
Personal Protection	X	3-High
		4-Extreme

Packaging

1 gal. 952793PL

175 Anderson Street, Aberdeen, NC 28315-1227 Phone: 800-982-7141 Fax: 910-944-7409 www.powerboss.com
For Technical Service, call: 1-800-433-6816 or e-mail: chemical@minutemanintl.com

WARNING & DISCLAIMER: Results may vary. PowerBoss chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Form 999505-6